Lynx-TE FSD

SA LYNX-TE 26W/830 FSD

0027854

Range features

- Triple pin-base lamps for traditional fixtures, new installations and downlights
- Suitable for operation on electronic control gear
- Excellent colour rendering - (CRI= 80-89)
- Rapid Run-up
- Dimmable with suitable dimmer
- Available in Warm White (3000K and Cool White (4000K)
- Average Rated Life 15000 hrs

PRODUCT OVERVIEW

Ordering number	0027854
Technology	Compact Fluorescent
Light colour	830 Warm White
Energy class	A
Average life (Rated) (h)	15000
Lamp shape	Stick
Lamp finish	Frosted
Dimmable	NO
Cap/Base	GX24q-3
Type	Lynx TE
EAN code	5410288278544
CRI (Ra)	80
Colour temperature (K)	3000
Luminous flux (Rated) (lm)	1800
Efficacy (Rated) (lm/w)	66
Watt (Nominal) (W)	26
Voltage (V)	105

Lynx-TE FSD

SA LYNX-TE 26W/830 FSD

0027854

DATA TABLE

Lynx-TE FSD

SA LYNX-TE 26W/830 FSD

0027854

General data

Ordering number	0027854
Dry applications use only	yes
Technology	Compact Fluorescent
Energy class	A
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000
Lamp finish	Frosted
Lamp shape	Stick
Dimmable	NO
Cap/Base	GX24q-3
Type	Lynx TE
EAN code	5410288278544
E-number SE	8357431
E-number FI	4944139
Long description	Triple pin-base lamps for traditional fixtures, new installations and downlights. Suitable for operation on electronic control gear. Excellent colour rendering - (CRI= 80-89). Rapid Run-up. Dimmable with suitable dimmer. Available in Warm White (3000K and Cool White (4000K). Average Rated Life 15000 hrs
Product name	SA LYNX-TE 26W/830 FSD
Lamp mercury content (mg)	< 2.50 mg
Starting time (max) (s)	10 Sec
Control gear required	Yes
IEC Reference	IEC 60901
IEC Reference 2	IEC 61199
IEC Reference 3	IEC 60921
Intended purpose	General lighting
Special purpose lamp	No
Transformer required	No
Sales pack quantity	10
Rated survival factor at 2000 h 50Hz	0.99
Rated survival factor at 2000 h High Frequency	> 0.99
Rated survival factor at 4000 h 50Hz	0.98
Rated survival factor at 4000 h High Frequency	> 0.98
Rated survival factor at 6000 h 50Hz	0.93
Rated survival factor at 6000 h High Frequency	> 0.95
Rated survival factor at 8000 h 50Hz	0.88
Rated survival factor at 8000 h High Frequency	> 0.92
Rated survival factor at 12000 h 50Hz	0.7
Rated survival factor at 12000 h High Frequency	> 0.88
Rated survival factor at 16000 h 50Hz	> 0.60
Rated survival factor at 16000 h High Frequency	> 0.80

Lynx-TE FSD

SA LYNX-TE 26W/830 FSD

0027854

Rated survival factor at 20000 h 50Hz	> 0.25
Rated survival factor at 20000 h High Frequency	> 0.50

Optical data

Light colour	830 Warm White
CRI (Ra)	80
Colour temperature (K)	3000
Luminous flux (Rated) (lm)	1800
Luminous flux (Nominal) (lm)	1800
Ambient temperature for maximum luminous flux (°C)	25
Rated lumen maint. factor at 2000 h 50Hz	0.90
Rated lumen maint. factor at 4000 h 50Hz	0.84
Rated lumen maint. factor at 6000 h 50Hz	0.82
Rated lumen maint. factor at 8000 h 50Hz	0.81
Rated lumen maint. factor at 12000 h 50Hz	0.75
Rated lumen maint. factor at 16000 h 50Hz	> 0.78
Rated lumen maint. factor at 20000 h 50Hz	> 0.75
Rated lumen maint. factor at 2000 h High Frequency	> 0.92
Rated lumen maint. factor at 4000 h High Frequency	> 0.88
Rated lumen maint. factor at 6000 h High Frequency	> 0.86
Rated lumen maint. factor at 8000 h High Frequency	> 0.84
Rated lumen maint. factor at 12000 h High Frequency	> 0.80
Rated lumen maint. factor at 16000 h High Frequency	> 0.78
Rated lumen maint. factor at 20000 h High Frequency	> 0.75

Electrical data

kWh per 1000 hours burning time	31
Efficacy (Rated) (lm/w)	66
Rated lamp efficacy (lm/W) 100H 50Hz at optimum temp.	66
Watt (Rated) (W)	26
Watt (Nominal) (W)	26
Voltage (V)	105
Ignition voltage (V)	0
Current (A)	0.325

Lynx-TE FSD

SA LYNX-TE 26W/830 FSD

0027854

Physical data

Weight (kg)	0.08
Length base to base (mm) - A	132
Lamp Length (mm) - C/L	116
Max. Lamp Diameter (mm) - D	49
Single packaging type	Box/Sleeve
Single package dimensions (L x W x H) (cm)	5.10 x 4.70 x 14.20
Outer package dimensions (L x W x H) (cm)	26.70 x 10.30 x 15.60

Lynx-TE FSD

SA LYNX-TE 26W/830 FSD

0027854

TECHNICAL DRAWINGS



ENERGY LABEL